





FB-FL-60WC1



- Field-Bright™ LUNENTEC® tuned spectrum
- Very light weight
- Color Rendition Index (CRI) > .95
- 100,000 hour life cycle
- 110V ~ 277V auto-sensing ballast
- Instant strike/re-strike
- Large format full dispersion light source
- Full diffusion nano particle reflector
- Powder-coated all-weather aluminum
- IP65 rated WF2 anti-corrosion grade



The Field-Bright™ 60-Watt mini flood is ideal for all types of fields, outdoor courts, parks, golf ranges, running tracks, recreational facilities, and even parking lots. The unique full spectrum full diffusion lamp is capable of replacing 250-watt high pressure sodium and metal halide fixtures for energy savings of up to 70% including ballast overhead. Full cut-off and dispersion geometry minimizes light pollution. Mercury is a solid encapsulated amalgam that makes Field-Bright™ environmentally friendly and safe. No special handling is required. No hazardous material disposal is necessary.

Field-Bright™ lights use proprietary LUNENTEC® spectral tuning for stunning resolution and contrast on green grass or Astroturf®, black pavement, red/brown clay and Hardtrue®



surfaces with very low energy consumption. Instant strike means never having to wait for a warm-up or cool-down. The FB-FL-60WC1 is even animal friendly and will not disturb nocturnal wildlife such as owls. Equally important, it is a neighbor-friendly fixture that can be focused away from surrounding buildings and homes. Field-Bright™ lights are not affected by temperature. The extraordinary 100,000 hour life cycle can lower maintenance costs by as much as 600% over conventional outdoor lighting systems.

Contact: Philip Gotthelf • (201) 784-1233 x 100 (office) • (201) 401-6068 (cell)
PO Box 566, Closter, NJ 07624-0566

ULTRA-TECH™ LIGHTING



TECHNICAL SPECIFICATIONS

MODEL	FB-FL-60WC1
RATED WATTAGE	60W
VOLTAGE RANGE	120V~277V \pm 15%
CURRENT	0.5102A~0.2210A
FREQUENCY	50/60Hz
POWER FACTOR	0.98
IN-RUSH CURRENT	NEGLIGIBLE
RFI PART 15/18	SHIELDED
NOISE	<20dB
TYPE	MAGNETIC INDUCTION
COLOR RENDITION INDEX	> .95
COLOR TEMPERATURE	~6500K UV TRUNCATED
CERTIFICATIONS	UL/UL-C/CCC/CE/FC/RoHS/CB
B.U.G. RATING	0/0/<110
DARK SKY	COMPLIANT G(0)
UL-C	WET LOCATION
TEMPERATURE RANGE	-30°F ~ +140°F
RATING	IP65 WF2 ANTI-CORROSION
FINISH	WF2 ANTI-CORROSION
REFLECTOR	FULL-DIFFUSION NANO-PARTICLE
WIND RATING U-BRACKET	75mph ~ 100mph gust
WIND RATING SLIP-FITTER	NOT AVAILABLE
LUMENS PER WATT	95LPW~105LPW
VISUALLY EFFECTIVE LUMENS	277/W

FEATURES	MH	HPS	LED	Snow-Bright™	Other MIL
100,000 hour lifecycle (11 yrs @ 24hrs/365 days)	No	No	No	YES	Yes
Up to 85% energy savings	< 30%	None	Some	YES	Some
LUMENTEC® Technology	No	No	No	YES	No
Proprietary VARI-BEAM® Reflector Geometry	No	No	No	YES	No
Instant strike - no warm up or cool down	No	No	Yes	YES	Yes
Full Spectrum with CRI > .95	Few	No	No	YES	Some
Color Temperatures > 6,500K	Rare	No	Rare	YES	Some
Exceptionally high power factor > .95	No	No	Some	YES	Some
Negligible "In-Rush" current	No	No	No	YES	YES
Unparalleled Warranty 5 years 50K hrs	No	No	Some	YES	Some
Fully recyclable, no special disposal	No	No	No	YES	Yes
Lease Financing Available	No	No	No	YES	No

